

Kit 401 Series Installation Instructions for Metal Posts


A. Drill Posts

Hole sizes through intermediate posts
and/or cable braces are:


5/32" for 1/8" cable
7/32" for 3/16" cable

End posts:

Drill and tap 5/16-24
threaded holes on the
inside of each end post.



All holes should be
burr-free.



B. Install Tensioning Terminal

1. Install the Adjust-A-Body® with Threaded Bolt Tensioner by threading the short end of the bolt into the pre-tapped hole in your end post using a 1/4" open-end wrench. (Figure 1)
2. Screw the lock nut all the way onto the 2"-long threaded end of the bolt. (Figure 2) Note: turn counter-clockwise to tighten/tension/close.
3. Slide the body of the Adjust-a-Body® with Threaded Bolt Tensioner onto the bare end of the cable, threaded end first, and pull it the length of the cable until it is stopped by the ferrule already swaged onto the cable. (Figure 3)
4. Thread the body (with the cable attached) onto the Threaded Bolt and turn 8 turns onto the male threads. (Figure 4)



Figure 1




Figure 2




Figure 3





Figure 4

C. Feed Cable through Intermediate Posts

1. Feed the bare end of the cable through all your intermediate posts and through the end post where you will be installing the Push-Lock® fitting.




D. Feed/Crimp Cable through Corner Posts

When passing cable railing through a corner, do not bend the cable past 45° at any time.


If turning 90°, a 2-step turn using a double corner post configuration is required, as illustrated. For wood frame cable runs with up to 90° of turn, kits with single tensioners are sufficient. If going through corners totaling more than 90°, you will want to use a kit with tensioners at both ends.

Corners require two posts because the cable itself, being rigid, will not cooperate in bending cleanly through a single post. When you go through a corner post, you will need to prevent the cable from slicing into the wood as it exits the post on an angle by using a Post Protector Tube.


1. Insert a Post Protector Tube (order separately from Accessories) into all wood posts where the cable angles out of the post. Drill 1/4" diameter holes 1-1/2" deep into the face of the post where each cable angles out of the post. Force tube into post so it is flush with post face. (Illustration D-1)




2. As you feed the bare end of your cable through your intermediate posts (per Section C in your installation instructions), stop after you feed it through the first of your two corner posts.
3. Mark the cable at the point where it exits the Post Protector Tube at the face of the first post. (Illustration D-2)



- Take a measurement in a straight line between the installed Post Protector Tubes on adjacent posts. Make a second mark on the cable that is the same distance away from the first mark as the measurement that you have just taken. (Illustration D-3)




- Remove the stud or the Adjust-A-Body from the tensioning terminal end that was installed in Section B of your kit instructions. This will make it possible to pull the first mark away from the face of the post so that you can access the mark for bending the cable. (Illustration D-4)



- Bend the cable in both locations that you have marked to approximately 45° (in the same plane). Use a tool such as Ultra-tec Cable Gripping Pliers to help you make "sharp" bends in your cables at the marked locations. (Illustration D-4)

- Re-attach the tensioning terminal such that the first mark is at the face of the post with the Post Protector Tube. Feed the bare end of the cable through the second post and continue to feed the cable through all other intermediate posts and/or another corner section. Pull tight until the second mark contacts the Post Protector Tube on the second post. (Illustration D-5)



- When the bare end of the cable has been passed through all remaining intermediate posts (if another 2-post corner is encountered, repeat Steps 1-7) proceed to Section E of the installation instructions for your kit application.



Installation Instructions / Step 5 continued for corners

When taking cable railing through a corner, do not bend the cable past 45° at any time.


If turning 90°, a 2-step turn using a double corner post configuration is required, as illustrated. For metal frame cable runs with up to 90° of turn, kits with single tensioners are sufficient. If going through corners totaling more than 90°, you will want to use a kit with tensioners at both ends.

Corners require two posts because the cable itself, being rigid, will not cooperate in bending cleanly through a single post.


- 5a. As you feed the bare end of your cable through your intermediate posts, stop after you feed it through the first of your two corner posts.
- 5b. Mark the cable at the point where it exits the face of the first post. (Illustration D-2)



5c. Take a measurement in a straight line between the adjacent posts. Make a second mark on the cable that is the same distance away from the first mark as the measurement that you have just taken. (Illustration D-3)




5d. Remove the stud from the tensioning terminal end that was installed in Section B of your kit instructions. This will make it possible to pull the first mark away from the face of the post so that you can access the mark for bending the cable. (Illustration D-4)



5e. Bend the cable in both locations that you have marked to approximately 45° (on the same plane). Use a tool such as Ultra-tec Cable Gripping Pliers to help you make “sharp” bends in your cables at the marked locations. (Illustration D-4)

5f. Re-attach the tensioning terminal to the point that the first mark is at the face of the first corner post. Feed the bare end of the cable through the second post and continue to feed the cable through all other intermediate posts and/or another corner section. Pull tight until the second mark contacts the second post. (Illustration D-5)



5g. When the bare end of the cable has been passed through all remaining intermediate posts (and maybe one more 2-post corner configuration) proceed to Step 6 of the installation instructions for your kit application.

E. Install Swageless Terminal


1. Start the Push-Lock® body threads into the pre-tapped post by hand.



2. Thread the Push-Lock® coupler onto the post and tighten with 7/16" wrench.



3. Pull the cable tightly along the side of the fitting and mark the cable 1-3/16" from the end of the fitting opposite the post. Mark and cut the cable on your mark.



4. At opposite end post with tensioning terminal, detach the body from the Threaded Bolt to allow cable slack so you can perform the next step.

5. Back at post with swageless terminal, , push the cable into the hole in the fitting as far as it will go (approx. 1-1/16"). Twist the cable in a right hand direction as you push it into the fitting.




Note: If you have trouble inserting the cable into the fitting, it may be because the locking wedges have become stuck. This is not a defect! Here's what you can do to "free the wedges" —
For Pull-Lock® or Push-Lock® fittings for 1/8" cable, using either a PL-KEY or 1/4" diameter bolt, insert the PL-KEY or bolt into the hole and press until the wedges move freely. Perform the same operation for a 3/16" Pull-Lock® or Push-Lock®, except use a 16d nail or another tool with 1/8" or smaller diameter. Anything larger than what is recommended can actually get stuck inside the fitting - NOT what you want!

6. Return to the post with tensioning terminal and hand turn the body back onto the Threaded Bolt as far as possible.

F. Tension Cables

1. Tension the cable by holding it to prevent the cable from turning while you turn the Adjust-A-Body® with a 7/16" open-end wrench. Be careful to protect the cable from damage while tensioning the Adjust-A-Body®.

2. Tension all cables to desired amount in sequence, beginning with the center cables, moving up and down toward the top and bottom. As you tension each cable, give it a sharp pull downward mid-span to help set the wedges, then re-tension as necessary in the same sequence.



3. While holding the body still with a 7/16" open-end wrench, turn the lock nut against the body and tighten with a wrench.

